

Monteringsvägledning


SE_600-1500_40998516_V1



 Max. 65°C, 150°F


Max:	l/min.	Gal/min.
600:	65	17.2
700V:	65	17.2
800V:	34	9.0
900:	30	8.0
1500:	65	17.2

Min. 15 mm
Max 65 mm



600/700/800/1500		VR697		VR1400		VR2019
Tiles: Fliesen: Fliser: Tegels: Carreaux:	5 - 15 mm	Std.	+	Std.	+	Std.
	15 - 25 mm	+10 STANDARD SVERIGE				
	25 - 35 mm	+20	+	+20	+	+20
	35 - 45 mm	+30		+30		+30
	45 - 55 mm	+40		+40		+40
	55 - 65 mm	+50		+50		+50


58 - 0 mm




* +10 - STANDARD SVERIGE

		VR697		VR1400		VR2019
	46 - 58 mm	Std.	+	Std.	+	Std.
	36 - 50 mm	+10		+10		+10
	26 - 40 mm	+20		+20		+20
	16 - 30 mm	+30		+30		+30
	6 - 20 mm	+40		+40		+40
	(-4) - 10 mm	+50		+50		+50


VR697+










VR2019+, VR2119+



VR1400+











	L	L1	H
A	318 mm 12 1/2"	78 mm 3 1/16"	95 mm 3 3/4"
B			
C			
D	220 mm 8 1/2"		
E			
F		396 mm 15 1/2"	
G	120 mm 4 3/4"	-	



1 Demontera sidofixturerna.
Ta inte bort ljudisolering och Skyddskåpor.

NB.
Boxen levereras inte av VOLA.
Utan köps genom ÅF eller Grossist.



VOLA 200M

Fitting instruction
Montageanleitung
Monteringsvejledning

Monteringsvægledning
Montage hanleiding
Manuel de montage

www.vola.com

200M_V2_40998506

VR968: To be ordered separately.
Werden separat bestellt.
Bestilles separat.
Beställs separat.
Apart te bestellen.
À commander séparément.

Box till inbyggnadsblandare.
Boks til indbygningsblander.
Laatikko seinäasenteiselle sekoittajalle.

Ingår inte i leveransen, köps separat.
Ikke inkludert, kjøpes separat.
Eivät sisälly tilaukseen, ostettava erikseen.

Max.: 10 Bar/145 psi

Max. 65°C, 150°F

Check the local legislation.
Bitte die örtlichen Vorschriften überprüfen.
Tjek de lokale regler.
Kontrollera lokala föreskrifter
Nazitten lokale regelgeving.
Vérifiez la législation locale.

200M & VR968:

Extension
Verlängerung
Förlängning
Modification

VR2019: 010, 020, 030, 040/B, 050K, 070/R/S/W, 080/K/D/DK
VR2020: 080W
VR2119: 010C, 020C, 040D
VR2219: 050, 050A, 060A
VR648: 060, 080ST

VR2019:
VR2020:
VR2119:
VR2219:

VR648:

VR2019, VR2020, VR2119, VR2219		
Tiles:	3 - 15 mm	Std.
Fliesen:	15 - 25 mm	+10*
Fliser:	25 - 35 mm	+20
Tegels:	35 - 45 mm	+30
Carreaux:	45 - 55 mm	+40
	55 - 65 mm	+50

VR648:		
Tiles:	3 - 19 mm	Std.
Fliesen:	17 - 28 mm	+10*
Fliser:	27 - 38 mm	+20
Fliser:	37 - 48 mm	+30
Tegels:	47 - 58 mm	+40
Carreaux:	57 - 68 mm	+50


* +10 - STANDARD SVERIGE

Installation example
Installationsbeispiel
Installationsexempel
l'installation des exemple

Fitting of extension
Montage von verlängerung
Montering af forlængerdele
Montering av förlängning
Montage van de verlengstukken
Montage des rallonges


VR2019+, VR2119+
VR2020+, VR2219+

VR648+



2x13 mm Lightweight wall
Leichtwand
Let væg


Lätta konstruktion
Holle wandconstructie
Construction légère



1x15 mm
1x18 mm
1x20 mm


Lightweight wall
Leichtwand
Let væg

Lätta konstruktion
Holle wandconstructie
Construction légère



Masonry
Mauerwerk
Murværk

Murverk
Massieve wand
Mur Plein











2


Test Pressure
Prüfdruck
testtryk
Test tryk
Test druk
test de pression

Check the local legislation.
Bitte die örtlichen Vorschriften überprüfen.
Tjek de lokale regler.
Kontrollera lokala föreskrifter.
Nazitten lokale regelgeving.
Vérifiez la législation locale.

! Water - Wasser - Vand - Vatten - Water - L'eau
! MAX 1 Minute - Minut - Minuut !


1. MAX. 16 Bar 232 Psi
2. MAX. 4 Bar 58 Psi





NR17: VR2A, VR23, VR665, VR667
 NR19: VR2A, VR23, VR665, VR1419
 VR697K: VR21, VR23, VR666, VR669, VR697
 VR1400: VR21, VR23, VR406, VR1902, VR2213

800V	800NV	800TV
1037	004	
3x001G	3x001G, 001	



vola
 Lunavej 2
 DK-8700 Horsens
 Tlf : + 45 7023 5500
 sales@vola.com
 www.vola.com

VOLA 800V
 800NV, 800TV

Date
 May 22

Rev.
 5

Sheet
 SB 7.3